

A: Datasheet

Algorithm: paravision_007

Developer: Paravision (EverAI)

Submission Date: 2021_02_01

Template size: 4096 bytes

Template time (2.5 percentile): 700 msec

Template time (median): 701 msec

Template time (97.5 percentile): 711 msec

Investigation:

Frontal mugshot ranking 7 (out of 279) -- FNIR(1600000, 0, 1) = 0.0012 vs. lowest 0.0009 from sensetime_005

Mugshot webcam ranking 8 (out of 241) -- FNIR(1600000, 0, 1) = 0.0080 vs. lowest 0.0062 from sensetime_005

Mugshot profile ranking 4 (out of 210) -- FNIR(1600000, 0, 1) = 0.0661 vs. lowest 0.0587 from xforwardai_002

Immigration visa-border ranking 41 (out of 168) -- FNIR(1600000, 0, 1) = 0.0050 vs. lowest 0.0013 from visionlabs_010

Immigration visa-kiosk ranking 32 (out of 165) -- FNIR(1600000, 0, 1) = 0.1008 vs. lowest 0.0568 from cloudwalk_hr_000

Identification:

Frontal mugshot ranking 10 (out of 279) -- FNIR(1600000, T, L+1) = 0.0040, FPIR=0.001000 vs. lowest 0.0018 from sensetime_004


Mugshot webcam ranking 12 (out of 236) -- FNIR(1600000, T, L+1) = 0.0250, FPIR=0.001000 vs. lowest 0.0122 from sensetime_003

Mugshot profile ranking 187 (out of 209) -- FNIR(1600000, T, L+1) = 0.9999, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk_hr_000


Immigration visa-border ranking 13 (out of 167) -- FNIR(1600000, T, L+1) = 0.0086, FPIR=0.001000 vs. lowest 0.0047 from idemia_008

Immigration visa-kiosk ranking 154 (out of 162) -- FNIR(1600000, T, L+1) = 1.0000, FPIR=0.001000 vs. lowest 0.0996 from cloudwalk_hr_000


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime_004)



C: Evolution of accuracy for PARAVISION algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images


N 00640000 01600000 03000000 06000000 12000000



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_005)




L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T , $N = 1.6$ million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates.
 The bottom panels give high threshold for more lights-out identification with low FPIR.




P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: paravision_007, Dataset: Border–Crossing Ageing
Threshold: 3.039147 set to achieve FPIR(30–45, Male) = 0.001


Color encodes log(FPIR)

-4 -3 -2 -1



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

